

In re Application of:  
Frank Paetzold et al.  
Application No.: 09/929,516  
Filed: August 13, 2001  
Page 3

PATENT  
Docket No.: EYEM1340

**Claim Listing:**

---

1. (currently amended) Method for generating facial animation values using a sequence of facial image frames and synchronously captured audio data of a speaking actor, comprising the steps for:

providing a plurality of visual-facial-animation values based on tracking, without using markers attached to the actor's face, of facial features in the sequence of facial image frames of the speaking actor;

providing a plurality of audio-facial-animation values based on visemes detected using the synchronously captured audio voice data of the speaking actor; and

combining the plurality of visual facial animation values and the plurality of audio facial animation values to generate output facial animation values for use in facial animation.

2. (original) Method for generating facial animation values as defined in claim 1, wherein the output facial animation values associated with a mouth for a facial animation are based only on the respective mouth-associated values of the plurality of audio facial animation values.

3. (original) Method for generating facial animation values as defined in claim 1, wherein the output facial animation values associated with a mouth for a facial animation are based only on the respective mouth-associated values of the plurality of audio facial animation values.

In re Application of:  
Frank Paetzold et al.  
Application No.: 09/929,516  
Filed: August 13, 2001  
Page 4

PATENT  
Docket No.: EYEM1340

4. (original) Method for generating facial animation values as defined in claim 1, wherein the output facial animation values associated with a mouth for a facial animation are based on Kalman filtering of the respective mouth-associated values of the plurality of visual facial animation values and the respective mouth-associated values of the plurality of audio facial animation values.

C 3  
5. (original) Method for generating facial animation values as defined in claim 1, wherein the step of combining the plurality of visual facial animation values and the plurality of audio facial animation values to generate output facial animation values includes detecting whether speech is occurring in the synchronously captured audio voice data of the speaking actor and, while speech is detected as occurring, generating the output facial animation values associated with a mouth based only on the respective mouth-associated values of the plurality of audio facial animation values and, while speech is not detected as occurring, generating the output facial animation values associated with a mouth based only on the respective mouth-associated values of the plurality of visual facial animation values.

6. (original) Method for generating facial animation values as defined in claim 1, wherein the tracking of facial features in the sequence of facial image frames of the speaking actor is performed using bunch graph matching.

7. (original) Method for generating facial animation values as defined in claim 1, wherein the tracking of facial features in the sequence of facial image frames of the speaking actor is performed using transformed facial image frames generated based on wavelet transformations.

In re Application of:  
Frank Paetzold et al.  
Application No.: 09/929,516  
Filed: August 13, 2001  
Page 5

PATENT  
Docket No.: EYEM1340

8. (original) Method for generating facial animation values as defined in claim 1, wherein the tracking of facial features in the sequence of facial image frames of the speaking actor is performed using transformed facial image frames generated based on Gabor wavelet transformations.

9. (currently amended) Apparatus for generating facial animation values using a sequence of facial image frames and synchronously captured audio data of a speaking actor, comprising:

means for providing a plurality of visual-facial-animation values based on tracking, without using markers attached to the speaking actor's face, of facial features in the sequence of facial image frames of the speaking actor;

C3 means for providing a plurality of audio-facial-animation values based on visemes detected using the synchronously captured audio voice data of the speaking actor; and

means for providing a plurality of visual-facial-animation values based on tracking of facial features in the sequence of facial image frames of the speaking actor;

means for combining the plurality of visual facial animation values and the plurality of audio facial animation values to generate output facial animation values for use in facial animation.

10. (original) Apparatus for generating facial animation values as defined in claim 9, wherein the output facial animation values associated with a mouth for a facial animation are based only on the respective mouth-associated values of the plurality of audio facial animation values.

In re Application of:  
Frank Paetzold et al.  
Application No.: 09/929,516  
Filed: August 13, 2001  
Page 6

PATENT  
Docket No.: EYEM1340

11. (original) Apparatus for generating facial animation values as defined in claim 9, wherein the output facial animation values associated with a mouth for a facial animation are based on a weighted average of the respective mouth-associated values of the plurality of visual facial animation values and the respective mouth-associated values of the plurality of audio facial animation values.

12. (original) Apparatus for generating facial animation values as defined in claim 9, wherein the output facial animation values associated with a mouth for a facial animation are based on Kalman filtering of the respective mouth-associated values of the plurality of visual facial animation values and the respective mouth-associated values of the plurality of audio facial animation values.

C3  
13. (original) Apparatus for generating facial animation values as defined in claim 9, wherein the means for combining the plurality of visual facial animation values and the plurality of audio facial animation values to generate output facial animation values includes means for detecting whether speech is occurring in the synchronously captured audio voice data of the speaking actor and, while speech is detected as occurring, generating the output facial animation values associated with a mouth based only on the respective mouth-associated values of the plurality of audio facial animation values and, while speech is not detected as occurring, generating the output facial animation values associated with a mouth based only on the respective mouth-associated values of the plurality of visual facial animation values.

14. (original) Apparatus for generating facial animation values as defined in claim 9, wherein the tracking of facial features in the sequence of facial image frames of the speaking actor is performed using bunch graph matching.

In re Application of:  
Frank Paetzold et al.  
Application No.: 09/929,516  
Filed: August 13, 2001  
Page 7

PATENT  
Docket No.: EYEM1340

15. (original) Apparatus for generating facial animation values as defined in claim 9, wherein the tracking of facial features in the sequence of facial image frames of the speaking actor is performed using transformed facial image frames generated based on wavelet transformations.

C3

16. (original) Apparatus for generating facial animation values as defined in claim 9, wherein the tracking of facial features in the sequence of facial image frames of the speaking actor is performed using transformed facial image frames generated based on Gabor wavelet transformations.

---